

Data sheet

SM 021 (021-1DF00)

Technical data

| | |
|------------------|------------------|
| Order no. | 021-1DF00 |
| Type | SM 021 |
| Module ID | 0012 1F41 |

General information

| | |
|----------|--|
| Note | - |
| Features | 8 inputs diagnosis of wiring errors |

Current consumption/power loss

| | |
|--|-------|
| Current consumption from backplane bus | 60 mA |
| Power loss | 1.1 W |

Technical data digital inputs

| | |
|---|------------------------------|
| Number of inputs | 8 |
| Cable length, shielded | 1000 m |
| Cable length, unshielded | 600 m |
| Rated load voltage | - |
| Current consumption from load voltage L+ (without load) | - |
| Rated value | DC 20.4...28.8 V |
| Input voltage for signal "0" | DC 0...5 V |
| Input voltage for signal "1" | DC 10,8...28,8 V |
| Input voltage hysteresis | - |
| Frequency range | - |
| Input resistance | - |
| Input current for signal "1" | 3 mA |
| Connection of Two-Wire-BEROs possible | yes |
| Max. permissible BERO quiescent current | 1.5 mA |
| Input delay of "0" to "1" | parameterizable 100µs - 20ms |
| Input delay of "1" to "0" | parameterizable 100µs - 20ms |
| Number of simultaneously utilizable inputs horizontal configuration | 8 |
| Number of simultaneously utilizable inputs vertical configuration | 8 |
| Input characteristic curve | IEC 61131-2, type 3 |
| Initial data size | 8 Bit |

Status information, alarms, diagnostics

| | |
|----------------------------------|-----------------------|
| Status display | green LED per channel |
| Interrupts | yes |
| Process alarm | no |
| Diagnostic interrupt | yes, parameterizable |
| Diagnostic functions | yes |
| Diagnostics information read-out | possible |
| Module state | green LED |

| | |
|-----------------------|---------|
| Module error display | red LED |
| Channel error display | none |

Isolation

| | |
|------------------------------------|----------|
| Between channels | - |
| Between channels of groups to | - |
| Between channels and backplane bus | yes |
| Insulation tested with | DC 500 V |

Safety

| | |
|---------------------|---|
| Safety protocol | - |
| Safety requirements | - |
| Secure user address | - |
| Watchdog | - |
| Two channels | - |
| Test pulse outputs | - |

Datasizes

| | |
|------------------|----|
| Input bytes | 1 |
| Output bytes | 0 |
| Parameter bytes | 12 |
| Diagnostic bytes | 20 |

Housing

| | |
|----------|--------------------|
| Material | PPE / PPE GF10 |
| Mounting | Profile rail 35 mm |

Mechanical data

| | |
|--------------------|----------------------------|
| Dimensions (WxHxD) | 12.9 mm x 109 mm x 76.5 mm |
| Weight | 60 g |

Environmental conditions

| | |
|-----------------------|-----------------|
| Operating temperature | 0 °C to 60 °C |
| Storage temperature | -25 °C to 70 °C |

Certifications

| | |
|------------------|----------------|
| UL certification | in preparation |
| KC certification | yes |