

## Data sheet

### IM 208CAN, CANopen master (208-1CA00)

#### Technical data

<b>Order no.</b>	<b>208-1CA00</b>
------------------	------------------

Type	IM 208CAN, CANopen master
------	---------------------------

#### General information

Note	-
------	---

Features	CANopen master 125 CAN slaves connectable Project engineering under VIPA WinCoCT 40 Transmit PDOs, 40 Receive PDOs
----------	---

#### Current consumption/power loss

Current consumption from backplane bus	300 mA
--	--------

Power loss	1.5 W
------------	-------

#### Status information, alarms, diagnostics

Status display	yes
----------------	-----

Interrupts	yes, parameterizable
------------	----------------------

Process alarm	no
---------------	----

Diagnostic interrupt	yes, parameterizable
----------------------	----------------------

Diagnostic functions	yes
----------------------	-----

Diagnostics information read-out	possible
----------------------------------	----------

Supply voltage display	none
------------------------	------

Group error display	red LED
---------------------	---------

Channel error display	none
-----------------------	------

#### Functionality Sub-D interfaces

Type	-
------	---

Type of interface	CAN
-------------------	-----

Connector	Sub-D, 9-pin, male
-----------	--------------------

Electrically isolated	yes
-----------------------	-----

MPI	-
-----	---

MP21 (MPI/RS232)	-
------------------	---

Point-to-point interface	-
--------------------------	---

#### Housing

Material	PPE
----------	-----

Mounting	Profile rail 35 mm
----------	--------------------

#### Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
--------------------	-------------------------

Weight	80 g
--------	------

#### Environmental conditions

Operating temperature	0 °C to 60 °C
-----------------------	---------------

Storage temperature	-25 °C to 70 °C
---------------------	-----------------

#### Certifications

UL certification yes

KC certification -