

## Data sheet

### Touch Panel TP 608C (62I-JID0-CB)

#### Technical data

<b>Order no.</b>	<b>62I-JID0-CB</b>
------------------	--------------------

Type	Touch Panel TP 608C
------	---------------------

#### General information

Note	-
------	---

Features	8,4", TFT, 800x600 pixel XScale processor, 1.1GHz 256 MB work memory, 512 MB user memory MPI/PROFIBUS-DP, RS232, RS422/485, 2xUSB-A, USB-B, 2x Ethernet RJ45 Windows Embedded CE 6.0 Professional, Movicon Runtime
----------	--

#### Display

Display size (diagonal)	8.4 "
-------------------------	-------

Display size (width)	170.4 mm
----------------------	----------

Display size (height)	127.8 mm
-----------------------	----------

Resolution	600 x 800 / 800 x 600
------------	-----------------------

Aspect ratio	4:3
--------------	-----

Type of display	TFT color (16.7M colors)
-----------------	--------------------------

MTBF Backlights (25°C)	50000 h
------------------------	---------

#### System properties

Processor	Xscale 1.1 GHz
-----------	----------------

Operating system	Windows CE 6.0 Prof.
------------------	----------------------

User software	Movicon 11 CE Standard
---------------	------------------------

Work memory	256 MB
-------------	--------

User memory	512 MB
-------------	--------

Available memory (user data)	380 MB
------------------------------	--------

SD/MMC Slot	yes
-------------	-----

CF Card Slot Typ II	yes
---------------------	-----

CFast Slot	-
------------	---

#### Time

Real-time clock buffered	yes
--------------------------	-----

Clock buffered period (min.)	6 w
------------------------------	-----

Type of buffering	Vanadium Rechargeable Lithium Battery
-------------------	---------------------------------------

Load time for 50% buffering period	10 h
------------------------------------	------

Load time for 100% buffering period	48 h
-------------------------------------	------

Accuracy (max. deviation per day)	10 s
-----------------------------------	------

#### Operating controls

Touchscreen	resistive
-------------	-----------

Touch function	Single Touch
----------------	--------------

Keyboard	external via USB
----------	------------------

Mouse	external via USB
-------	------------------

#### Interfaces

MPI, PROFIBUS-DP	RS485 isolated
MPI, PROFIBUS-DP connector	Sub-D, 9-pin, female
Serial, COM1	RS232
COM1 connector	Sub-D, 9-pin, male
Serial, COM2	RS422/485 isolated
COM2 connector	Sub-D, 9-pin, female
Number of USB-A interfaces	2
USB-A connector	USB-A (host)
Number of USB-B interfaces	1
USB-B connector	USB-B (device)
Number of ethernet interfaces	2
Ethernet	Ethernet 10/100 MBit
Ethernet connector	RJ45
Integrated ethernet switch	yes
Video connectors	-
Audio connections	-

### Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	0.4 A
Current consumption (rated value)	0.6 A
Inrush current	7 A
I <sup>2</sup> t	0.25 A <sup>2</sup> s
Power loss	9.6 W

### Status information, alarms, diagnostics

Supply voltage display	yes
------------------------	-----

### Mechanical data

#### Housing / Protection type

Material	die-cast aluminum
Mounting	via integrated pivoted lever
Protect type front side	IP 65
Protect type back side	IP 20

#### Dimensions

Front panel	264 mm x 189 mm x 7.5 mm
Rear panel	248 mm x 173 mm x 43 mm

#### Installation cut-out

Width	250 mm
Height	175 mm
Minimum	1.5 mm
Maximum front panel thickness	6 mm
Weight	2325 g

#### Environmental conditions

Operating temperature	0 °C to 50 °C
-----------------------	---------------

Storage temperature -20 °C to 60 °C

---

### Certifications

---

UL certification in preparation

---

KC certification -

---