

Data sheet

TM-E Analog Router - VPN (900-2E641)

Technical data

Order no.	900-2E641
------------------	------------------

Type	TM-E Analog Router - VPN
------	--------------------------

General information

Note	-
------	---

Features	For direct point to point teleservice via analog line or Talk2M & VPN 1x RS485 MPI-/PROFIBUS-DP interface 1x LAN RJ45 Ethernet interface 1x integrated PSTN modem
----------	--

Inputs and outputs

Inputs	1 DI: 0/24 V DC, isolated
--------	---------------------------

Outputs	1 DO: open drain, max. 200 mA at DC 30 V
---------	--

Communication

serial port	MPI/PROFIBUS, isolated, up to 12 MBit/s
-------------	---

LAN	1 x RJ45, 10/100 MBit/s
-----	-------------------------

WAN	-
-----	---

Modem type	PSTN / analog
------------	---------------

Router

Router functions	IP-Forwarding IP-Filter NAT Port-Forwarding Routing Table DHCP-Client
------------------	--

RAS	PPP Dial-In PPP Dial-Out Call-Back
-----	--

VPN

VPN mode	Open VPN 2.0, Client/Server
----------	-----------------------------

Talk2M	yes
--------	-----

Gateway protocols	MPI PPI PROFIBUS ISO TCP Modbus TCP
-------------------	---

Services

Server services	FTP HTTP
-----------------	-------------

Client Services	FTP SMTP NTP DYNDNS SNMP
-----------------	--------------------------------------

Data management

Custom Website	yes
----------------	-----

Project	web interface
---------	---------------

Integrated protocols

MPI
PPI
PROFIBUS
ISO TCP
Modbus TCP

Interrupts

Alarm message	E Mail SMS SNMP FTP
Alarm	E Mail Hardware I/O SMS PLC-variables SNMP system variables FTP

Housing

Material	-
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	39 mm x 129 mm x 108 mm
Weight	400 g

Environmental conditions

Operating temperature	0 °C to 50 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	-
KC certification	-