





Machine Mounted Displays Stainless steel monitor for use in the food, beverage, pharmaceutical and chemical industries

Fully closed stainless steel housing, without screws and edges, optimised for high hygienic requirements: The new display of ADS-TEC has been developed and designed for machine and system operation in sensitive hygiene environments.





Machine Mounted Displays MMD9016



- → Easy to clean glass and stainless steel surfaces
- → Capacitive multi-touch display in 15.6" Full HD
- → Three different mounting options
- → Fully closed stainless steel housing
- → IP69K protection against dust and water jet

Easy to assemble Flexible mounting concept

- Three mounting options are available:
 - » Direct mounting (with optional spacer)
 - » VESA adapter
 - » Rotatable tube adapter for 48 mm support arm systems
- Foot or support arm mounting optional
- Horizontal or vertical alignment possible
- Compact design for convenient usage

Easy to clean Optimised for stringent hygiene requirements

- Standard cleaning agents can be used
- Easy to wipe and clean
- Preventing dirt and bacteria thanks to a screwless design without joints and edges



MMD9000 series

Operating temperature

Dimensions (W x H x D)

Humidity

Weight

| echnical Data | MMD9016 |
|------------------|---|
| Housing | Fully closed stainless steel housing |
| Display | 15.6" TFT LED backlight Full HD 1920 x 1080 pixels Typical brightness: 400 cd |
| Touch | PCAP multi-touch / tempered glass Optional: Shatter protection film |
| Interfaces | 1 x USB 2.0 Type A 1 x DisplayPort or 1 x USB 2.0 Type A 1 x HDMI |
| Power adapter | 24 VDC (tolerance 18 - 30 VDC) |
| Protection class | IP69K |

0 °C to +45 °C

10 to 85% non-condensing

4.5 kg (without adapter)

 $370 \times 239 \times 33 \text{ mm}$ (without adapter)

DZ-HAND-93234-1/A MMD9000 series Datasheet E11-2019

Industrial IT



